



Arch Wireless Level 2 with SLN Implementation Guide

X12/V4010/810: 810 Invoice

Version: 1.0

Author:	edi.support@arch.com
Publication:	12/2003
Notes:	This Implementation Guide provides summed charges at a Unit Level with supporting detail information making up the summed charge. Pager Phone/Pin Service ID Cap code/Pager Phone/Pin Serial Number



Table of Contents

Table of Contents	2
Invoice	3
Interchange Control Header	5
Functional Group Header	7
Transaction Set Header	9
Beginning Segment for Invoice	10
Reference Identification	11
Administrative Communications Contact	12
Loop N1	13
Name	14
Additional Name Information	15
Address Information	16
Geographic Location	17
Reference Identification	18
Date/Time Reference	19
Balance Detail	20
Loop IT1	21
Baseline Item Data (Invoice)	22
Tax Information	25
Loop SLN	26
Subline Item Detail	27
Date/Time Reference	31
Reference Identification	32
Product/Item Description	33
Tax Information	35
Loop N1	36
Name	37
Geographic Location	38
Reference Identification	39
Total Monetary Value Summary	40
Tax Information	41
Transaction Totals	42
Transaction Set Trailer	43
Functional Group Trailer	44
Interchange Control Trailer	45



810

Invoice

Functional Group=IN

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	ISA	Interchange Control Header	M	1			Must use
	GS	Functional Group Header	M	1			Must use

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	ST	Transaction Set Header	M	1			Must use
020	BIG	Beginning Segment for Invoice	M	1			Must use
050	REF	Reference Identification	O	12			Used
060	PER	Administrative Communications Contact	O	3			Used

<u>LOOP ID - N1</u>					<u>200</u>		
070	N1	Name	O	1			Used
080	N2	Additional Name Information	O	2			Used
090	N3	Address Information	O	2			Used
100	N4	Geographic Location	O	1			Used
110	REF	Reference Identification	O	12			Used
140	DTM	Date/Time Reference	O	10			Used
212	BAL	Balance Detail	O	>1			Used

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
<u>LOOP ID - IT1</u>					<u>200000</u>		
010	IT1	Baseline Item Data (Invoice)	O	1			Used
040	TXI	Tax Information	O	10			Used
<u>LOOP ID - SLN</u>					<u>1000</u>		
200	SLN	Subline Item Detail	O	1			Used
205	DTM	Date/Time Reference	O	1			Used
210	REF	Reference Identification	O	>1			Used
220	PID	Product/Item Description	O	1000			Used
237	TXI	Tax Information	O	10			Used
<u>LOOP ID - N1</u>					<u>200</u>		
240	N1	Name	O	1			Used
270	N4	Geographic Location	O	1			Used
280	REF	Reference Identification	O	12			Used

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	TDS	Total Monetary Value Summary	M	1			Must use
020	TXI	Tax Information	O	10			Used
070	CTT	Transaction Totals	O	1		N3/070	Used



080	SE	Transaction Set Trailer	M	1	Must use
-----	----	-------------------------	---	---	----------

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	GE	Functional Group Trailer	M	1			Must use
	IEA	Interchange Control Trailer	M	1			Must use

Notes:

3/070 Number of line items (CTT01) is the accumulation of the number of IT1 segments. If used, hash total (CTT02) is the sum of the value of quantities invoiced (IT102) for each IT1 segment.



ISA Interchange Control Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 16

User Option (Usage): Must use

To start and identify an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA01	I01	Authorization Information Qualifier Description: Code identifying the type of information in the Authorization Information All valid standard codes are used.	M	ID	2/2	Must use
ISA02	I02	Authorization Information Description: Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01)	M	AN	10/10	Must use
ISA03	I03	Security Information Qualifier Description: Code identifying the type of information in the Security Information All valid standard codes are used.	M	ID	2/2	Must use
ISA04	I04	Security Information Description: This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03)	M	AN	10/10	Must use
ISA05	I05	Interchange ID Qualifier Description: Code indicating the system/method of code structure used to designate the sender or receiver ID element being qualified All valid standard codes are used.	M	ID	2/2	Must use
ISA06	I06	Interchange Sender ID Description: Identification code published by the sender for other parties to use as the receiver ID to route data to them; the sender always codes this value in the sender ID element User Note 1: Production - EDIWIRELESS Test - EDIWIRELESSTEST	M	AN	15/15	Must use
ISA07	I05	Interchange ID Qualifier Description: Code indicating the system/method of code structure used to designate the sender or receiver ID element being qualified All valid standard codes are used.	M	ID	2/2	Must use
ISA08	I07	Interchange Receiver ID Description: Identification code published by the receiver of the data; When sending, it is used by the sender as their sending ID, thus other parties sending to them will use this as	M	AN	15/15	Must use



ISA09	I08	a receiving ID to route data to them Interchange Date Description: Date of the interchange	M	DT	6/6	Must use
ISA10	I09	Interchange Time Description: Time of the interchange	M	TM	4/4	Must use
ISA11	I65	Repetition Separator Description: Type is not applicable; the repetition separator is a delimiter and not a data element; this field provides the delimiter used to separate repeated occurrences of a simple data element or a composite data structure; this value must be different than the data element separator, component element separator, and the segment terminator	M		1/1	Must use
ISA12	I11	Interchange Control Version Number Description: Code specifying the version number of the interchange control segments All valid standard codes are used.	M	ID	5/5	Must use
ISA13	I12	Interchange Control Number Description: A control number assigned by the interchange sender	M	N0	9/9	Must use
ISA14	I13	Acknowledgment Requested Description: Code indicating sender's request for an interchange acknowledgment All valid standard codes are used.	M	ID	1/1	Must use
ISA15	I14	Interchange Usage Indicator Description: Code indicating whether data enclosed by this interchange envelope is test, production or information All valid standard codes are used.	M	ID	1/1	Must use
ISA16	I15	Component Element Separator Description: Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements within a composite data structure; this value must be different than the data element separator and the segment terminator	M		1/1	Must use



GS Functional Group Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 8

User Option (Usage): Must use

To indicate the beginning of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS01	479	Functional Identifier Code Description: Code identifying a group of application related transaction sets All valid standard codes are used.	M	ID	2/2	Must use
GS02	142	Application Sender's Code Description: Code identifying party sending transmission; codes agreed to by trading partners	M	AN	2/15	Must use
GS03	124	Application Receiver's Code Description: Code identifying party receiving transmission; codes agreed to by trading partners	M	AN	2/15	Must use
GS04	373	Date Description: Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year	M	DT	8/8	Must use
GS05	337	Time Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	M	TM	4/8	Must use
GS06	28	Group Control Number Description: Assigned number originated and maintained by the sender	M	N0	1/9	Must use
GS07	455	Responsible Agency Code Description: Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480 All valid standard codes are used.	M	ID	1/2	Must use
GS08	480	Version / Release / Industry Identifier Code Description: Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed	M	AN	1/12	Must use
		<u>Code</u> <u>Name</u>				



004010 Standards Approved for Publication by ASC X12 Procedures Review Board

Semantics:

1. GS04 is the group date.
2. GS05 is the group time.
3. The data interchange control number GS06 in this header must be identical to the same data element in the associated functional group trailer, GE02.

Comments:

1. A functional group of related transaction sets, within the scope of X12 standards, consists of a collection of similar transaction sets enclosed by a functional group header and a functional group trailer.



ST Transaction Set Header

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code Description: Code uniquely identifying a Transaction Set All valid standard codes are used.	M	ID	3/3	Must use
ST02	329	Transaction Set Control Number Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M	AN	4/9	Must use

Semantics:

1. The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).



BIG Beginning Segment for Invoice

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 4

User Option (Usage): Must use

To indicate the beginning of an invoice transaction set and transmit identifying numbers and dates

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BIG01	373	Date Description: Date expressed as CCYYMMDD	M	DT	8/8	Must use
BIG02	76	Invoice Number Description: Identifying number assigned by issuer	M	AN	1/22	Must use
BIG07	640	Transaction Type Code Description: Code specifying the type of transaction	O	ID	2/2	Used
		Code Name DI Debit Invoice				
BIG08	353	Transaction Set Purpose Code Description: Code identifying purpose of transaction set	O	ID	2/2	Used
		Code Name 00 Original				

Semantics:

1. BIG01 is the invoice issue date.
2. BIG03 is the date assigned by the purchaser to purchase order.
3. BIG10 indicates the consolidated invoice number. When BIG07 contains code CI, BIG10 is not used.

Comments:

1. BIG07 is used only to further define the type of invoice when needed.



REF Reference Identification

Pos: 050	Max: 12
Heading - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Used

To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier Description: Code qualifying the Reference Identification	M	ID	2/3	Must use
		Code Name IK Invoice Number				
REF02	127	Reference Identification Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X	AN	1/30	Used

Syntax:

1. R0203 - At least one of REF02,REF03 is required

Semantics:

1. REF04 contains data relating to the value cited in REF02.



PER Administrative Communications Contact

Pos: 060	Max: 3
Heading - Optional	
Loop: N/A	Elements: 3

User Option (Usage): Used

To identify a person or office to whom administrative communications should be directed

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PER01	366	Contact Function Code Description: Code identifying the major duty or responsibility of the person or group named	M	ID	2/2	Must use
		Code Name BI Bill Inquiry Contact				
PER03	365	Communication Number Qualifier Description: Code identifying the type of communication number	X	ID	2/2	Used
		Code Name TE Telephone UR Uniform Resource Locator (URL)				
PER04	364	Communication Number Description: Complete communications number including country or area code when applicable	X	AN	1/80	Used

Syntax:

1. P0304 - If either PER03,PER04 is present, then all are required
2. P0506 - If either PER05,PER06 is present, then all are required
3. P0708 - If either PER07,PER08 is present, then all are required



Loop N1

Pos: 070	Repeat: 200
Optional	
Loop: N1	Elements: N/A

To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
070	N1	Name	O	1		Used
080	N2	Additional Name Information	O	2		Used
090	N3	Address Information	O	2		Used
100	N4	Geographic Location	O	1		Used
110	REF	Reference Identification	O	12		Used



N1

Name

Pos: 070	Max: 1
Heading - Optional	
Loop: N1	Elements: 6

User Option (Usage): Used

To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code Description: Code identifying an organizational entity, a physical location, property or an individual	M	ID	2/3	Must use
		Code Name				
		RI Remit To				
		ST Ship To				
N102	93	Name Description: Free-form name	X	AN	1/60	Used
N103	66	Identification Code Qualifier Description: Code designating the system/method of code structure used for Identification Code (67) All valid standard codes are used.	X	ID	1/2	Used
N104	67	Identification Code Description: Code identifying a party or other code	X	AN	2/80	Used
N105	706	Entity Relationship Code Description: Code describing entity relationship All valid standard codes are used.	O	ID	2/2	Used
N106	98	Entity Identifier Code Description: Code identifying an organizational entity, a physical location, property or an individual All valid standard codes are used.	O	ID	2/3	Used

Syntax:

1. R0203 - At least one of N102,N103 is required
2. P0304 - If either N103,N104 is present, then all are required

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.



N2

Additional Name Information

Pos: 080	Max: 2
Heading - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

To specify additional names or those longer than 35 characters in length

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N201	93	Name Description: Free-form name	M	AN	1/60	Must use
N202	93	Name Description: Free-form name	O	AN	1/60	Used



N3 Address Information

Pos: 090	Max: 2
Heading - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

To specify the location of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N301	166	Address Information Description: Address information	M	AN	1/55	Must use
N302	166	Address Information Description: Address information	O	AN	1/55	Used



N4 Geographic Location

Pos: 100	Max: 1
Heading - Optional	
Loop: N1	Elements: 4

User Option (Usage): Used

To specify the geographic place of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	City Name Description: Free-form text for city name	O	AN	2/30	Used
N402	156	State or Province Code Description: Code (Standard State/Province) as defined by appropriate government agency	O	ID	2/2	Used
N403	116	Postal Code Description: Code defining international postal zone code excluding punctuation and blanks (zip code for United States)	O	ID	3/15	Used
N404	26	Country Code Description: Code identifying the country	O	ID	2/3	Used

Syntax:

1. C0605 - If N406 is present, then all of N405 are required

Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.



REF Reference Identification

Pos: 110	Max: 12
Heading - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier Description: Code qualifying the Reference Identification	M	ID	2/3	Must use
		Code Name 11 Account Number				
REF02	127	Reference Identification Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X	AN	1/30	Used

Syntax:

1. R0203 - At least one of REF02,REF03 is required

Semantics:

1. REF04 contains data relating to the value cited in REF02.



DTM Date/Time Reference

Pos: 140	Max: 10
Heading - Optional	
Loop: N/A	Elements: 3

User Option (Usage): Used

To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier Description: Code specifying type of date or time, or both date and time	M	ID	3/3	Must use
		Code Name				
		186 Invoice Period Start				
		187 Invoice Period End				
DTM02	373	Date Description: Date expressed as CCYYMMDD	X	DT	8/8	Used
DTM05	1250	Date Time Period Format Qualifier Description: Code indicating the date format, time format, or date and time format	X	ID	2/3	Used
		Code Name				
		D8 Date Expressed in Format CCYYMMDD				

Syntax:

1. R020305 - At least one of DTM02,DTM03,DTM05 is required
2. C0403 - If DTM04 is present, then all of DTM03 are required
3. P0506 - If either DTM05,DTM06 is present, then all are required



BAL Balance Detail

Pos: 212	Max: >1
Heading - Optional	
Loop: N/A	Elements: 3

User Option (Usage): Used

To identify the specific monetary balances associated with a particular account

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BAL01	951	Balance Type Code Description: Code indicating the type of balance	M	ID	1/2	Must use
		<u>Code</u> <u>Name</u>				
		A Adjustment				
		M Current Month				
		Y Year to Date				
BAL02	522	Amount Qualifier Code Description: Code to qualify amount	M	ID	1/3	Must use
		<u>Code</u> <u>Name</u>				
		5 Total Invoice Amount				
		BD Balance Due				
		BM Adjustments				
		GZ Total Finance Charge				
		J8 Ending Balance				
		J9 Beginning Balance				
		PB Billed Amount				
		PJ Past Due				
		RT Last Payment				
		ZZ Mutually Defined				
		AAN Tax-Federal				
		AAO Tax-Local				
		AAP Tax-State				
		BAP Total Amount Due				
BAL03	782	Monetary Amount Description: Monetary amount	M	R	1/18	Must use



Loop IT1

Pos: 010	Repeat: 200000
Optional	
Loop: IT1	Elements: N/A

To specify the basic and most frequently used line item data for the invoice and related transactions

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	IT1	Baseline Item Data (Invoice)	O	1		Used
040	TXI	Tax Information	O	10		Used
200		Loop SLN	O		1000	Used
240		Loop N1	O		200	Used



IT1

Baseline Item Data (Invoice)

Pos: 010	Max: 1
Detail - Optional	
Loop: IT1	Elements: 24

User Option (Usage): Used

To specify the basic and most frequently used line item data for the invoice and related transactions

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IT101	350	Assigned Identification Description: Alphanumeric characters assigned for differentiation within a transaction set	O	AN	1/20	Used
IT102	358	Quantity Invoiced Description: Number of units invoiced (supplier units)	X	R	1/10	Used
IT103	355	Unit or Basis for Measurement Code Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken <u>Code</u> <u>Name</u> EA Each	X	ID	2/2	Used
IT104	212	Unit Price Description: Price per unit of product, service, commodity, etc.	X	R	1/17	Used
IT106	235	Product/Service ID Qualifier Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234) <u>Code</u> <u>Name</u> VP Vendor's (Seller's) Part Number	X	ID	2/2	Used
IT107	234	Product/Service ID Description: Identifying number for a product or service	X	AN	1/48	Used
IT108	235	Product/Service ID Qualifier Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234) <u>Code</u> <u>Name</u> ZP Pager Phone Number	X	ID	2/2	Used
IT109	234	Product/Service ID Description: Identifying number for a product or service	X	AN	1/48	Used
IT110	235	Product/Service ID Qualifier Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234) <u>Code</u> <u>Name</u> ZO Pager Pin Number	X	ID	2/2	Used
IT111	234	Product/Service ID Description: Identifying number for a product or service	X	AN	1/48	Used



IT112	235	Product/Service ID Qualifier Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234) Code Name SN Serial Number	X	ID	2/2	Used
IT113	234	Product/Service ID Description: Identifying number for a product or service	X	AN	1/48	Used
IT114	235	Product/Service ID Qualifier Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234) Code Name ZC Cap Code	X	ID	2/2	Used
IT115	234	Product/Service ID Description: Identifying number for a product or service	X	AN	1/48	Used
IT116	235	Product/Service ID Qualifier Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234) Code Name ZS RCC Number	X	ID	2/2	Used
IT117	234	Product/Service ID Description: Identifying number for a product or service	X	AN	1/48	Used
IT118	235	Product/Service ID Qualifier Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234) Code Name RZ Related Model Type	X	ID	2/2	Used
IT119	234	Product/Service ID Description: Identifying number for a product or service	X	AN	1/48	Used
IT120	235	Product/Service ID Qualifier Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234) Code Name EJ Service Feature ID	X	ID	2/2	Used
IT121	234	Product/Service ID Description: Identifying number for a product or service	X	AN	1/48	Used
IT122	235	Product/Service ID Qualifier Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234) Code Name CR Contract Number	X	ID	2/2	Used
IT123	234	Product/Service ID Description: Identifying number for a product or service	X	AN	1/48	Used
IT124	235	Product/Service ID Qualifier Description: Code identifying the type/source of the descriptive number used in	X	ID	2/2	Used



Product/Service ID (234)

	<u>Code</u>	<u>Name</u>				
	ZZ	Mutually Defined				
IT125	234	Product/Service ID	X	AN	1/48	Used
		Description: Identifying number for a product or service				

Syntax:

1. P020304 - If either IT102,IT103,IT104 is present, then all are required
2. P0607 - If either IT106,IT107 is present, then all are required
3. P0809 - If either IT108,IT109 is present, then all are required
4. P1011 - If either IT110,IT111 is present, then all are required
5. P1213 - If either IT112,IT113 is present, then all are required
6. P1415 - If either IT114,IT115 is present, then all are required
7. P1617 - If either IT116,IT117 is present, then all are required
8. P1819 - If either IT118,IT119 is present, then all are required
9. P2021 - If either IT120,IT121 is present, then all are required
10. P2223 - If either IT122,IT123 is present, then all are required
11. P2425 - If either IT124,IT125 is present, then all are required

Semantics:

1. IT101 is the purchase order line item identification.

Comments:

1. Element 235/234 combinations should be interpreted to include products and/or services. See the Data Dictionary for a complete list of IDs.
2. IT106 through IT125 provide for ten different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.



TXI Tax Information

Pos: 040	Max: 10
Detail - Optional	
Loop: IT1	Elements: 2

User Option (Usage): Used

To specify tax information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TXI01	963	Tax Type Code Description: Code specifying the type of tax	M	ID	2/2	Must use
		Code Name				
		FT Federal Excise Tax				
		LO Local Tax (Not Sales Tax)				
		ST State Sales Tax				
TXI02	782	Monetary Amount Description: Monetary amount	X	R	1/18	Used

Syntax:

1. R020306 - At least one of TXI02, TXI03, TXI06 is required
2. P0405 - If either TXI04, TXI05 is present, then all are required
3. C0803 - If TXI08 is present, then all of TXI03 are required

Semantics:

1. TXI02 is the monetary amount of the tax.
2. TXI03 is the tax percent expressed as a decimal.
3. TXI07 is a code indicating the relationship of the price or amount to the associated segment.



Loop SLN

Pos: 200	Repeat: 1000
Optional	
Loop: SLN	Elements: N/A

To specify product subline detail item data

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
200	SLN	Subline Item Detail	O	1		Used
205	DTM	Date/Time Reference	O	1		Used
210	REF	Reference Identification	O	>1		Used
220	PID	Product/Item Description	O	1000		Used
237	TXI	Tax Information	O	10		Used



SLN Subline Item Detail

Pos: 200	Max: 1
Detail - Optional	
Loop: SLN	Elements: 26

User Option (Usage): Used

To specify product subline detail item data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SLN01	350	Assigned Identification Description: Alphanumeric characters assigned for differentiation within a transaction set	M	AN	1/20	Must use
SLN02	350	Assigned Identification Description: Alphanumeric characters assigned for differentiation within a transaction set	O	AN	1/20	Used
SLN03	662	Relationship Code Description: Code indicating the relationship between entities	M	ID	1/1	Must use
		Code Name O Information Only				
SLN04	380	Quantity Description: Numeric value of quantity	X	R	1/15	Used
SLN05	C001	Composite Unit of Measure Description: To identify a composite unit of measure(See Figures Appendix for examples of use)	X	Comp		Used
	355	Unit or Basis for Measurement Code Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken All valid standard codes are used.	M	ID	2/2	Must use
	1018	Exponent Description: Power to which a unit is raised	O	R	1/15	Used
	649	Multiplier Description: Value to be used as a multiplier to obtain a new value	O	R	1/10	Used
	355	Unit or Basis for Measurement Code Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken All valid standard codes are used.	O	ID	2/2	Used
	1018	Exponent Description: Power to which a unit is raised	O	R	1/15	Used
	649	Multiplier Description: Value to be used as a multiplier to obtain a new value	O	R	1/10	Used
	355	Unit or Basis for Measurement Code Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken All valid standard codes are used.	O	ID	2/2	Used



	1018	Exponent Description: Power to which a unit is raised	O	R	1/15	Used
	649	Multiplier Description: Value to be used as a multiplier to obtain a new value	O	R	1/10	Used
	355	Unit or Basis for Measurement Code Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken All valid standard codes are used.	O	ID	2/2	Used
	1018	Exponent Description: Power to which a unit is raised	O	R	1/15	Used
	649	Multiplier Description: Value to be used as a multiplier to obtain a new value	O	R	1/10	Used
	355	Unit or Basis for Measurement Code Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken All valid standard codes are used.	O	ID	2/2	Used
	1018	Exponent Description: Power to which a unit is raised	O	R	1/15	Used
	649	Multiplier Description: Value to be used as a multiplier to obtain a new value	O	R	1/10	Used
SLN06	212	Unit Price Description: Price per unit of product, service, commodity, etc.	X	R	1/17	Used
SLN09	235	Product/Service ID Qualifier Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234) Code Name VP Vendor's (Seller's) Part Number	X	ID	2/2	Used
SLN10	234	Product/Service ID Description: Identifying number for a product or service	X	AN	1/48	Used
SLN11	235	Product/Service ID Qualifier Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234) Code Name ZP Pager Phone Number	X	ID	2/2	Used
SLN12	234	Product/Service ID Description: Identifying number for a product or service	X	AN	1/48	Used
SLN13	235	Product/Service ID Qualifier Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234) Code Name ZO Pager Pin Number	X	ID	2/2	Used
SLN14	234	Product/Service ID Description: Identifying number for a product or service	X	AN	1/48	Used
SLN15	235	Product/Service ID Qualifier Description: Code identifying the	X	ID	2/2	Used



		type/source of the descriptive number used in Product/Service ID (234)					
		<u>Code</u>	<u>Name</u>				
		SN	Serial Number				
SLN16	234	Product/Service ID		X	AN	1/48	Used
		Description: Identifying number for a product or service					
SLN17	235	Product/Service ID Qualifier		X	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)					
		<u>Code</u>	<u>Name</u>				
		ZC	Cap Code				
SLN18	234	Product/Service ID		X	AN	1/48	Used
		Description: Identifying number for a product or service					
SLN19	235	Product/Service ID Qualifier		X	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)					
		<u>Code</u>	<u>Name</u>				
		ZS	RCC Number				
SLN20	234	Product/Service ID		X	AN	1/48	Used
		Description: Identifying number for a product or service					
SLN21	235	Product/Service ID Qualifier		X	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)					
		<u>Code</u>	<u>Name</u>				
		RZ	Related Model Type				
SLN22	234	Product/Service ID		X	AN	1/48	Used
		Description: Identifying number for a product or service					
SLN23	235	Product/Service ID Qualifier		X	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)					
		<u>Code</u>	<u>Name</u>				
		EJ	Service Feature ID				
SLN24	234	Product/Service ID		X	AN	1/48	Used
		Description: Identifying number for a product or service					
SLN25	235	Product/Service ID Qualifier		X	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)					
		<u>Code</u>	<u>Name</u>				
		CR	Contract Number				
SLN26	234	Product/Service ID		X	AN	1/48	Used
		Description: Identifying number for a product or service					
SLN27	235	Product/Service ID Qualifier		X	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)					
		<u>Code</u>	<u>Name</u>				



SLN28	234	ZZ	Mutually Defined					
			Product/Service ID	X	AN	1/48		Used
			Description: Identifying number for a product or service					

Syntax:

1. P0405 - If either SLN04,SLN05 is present, then all are required
2. C0706 - If SLN07 is present, then all of SLN06 are required
3. C0806 - If SLN08 is present, then all of SLN06 are required
4. P0910 - If either SLN09,SLN10 is present, then all are required
5. P1112 - If either SLN11,SLN12 is present, then all are required
6. P1314 - If either SLN13,SLN14 is present, then all are required
7. P1516 - If either SLN15,SLN16 is present, then all are required
8. P1718 - If either SLN17,SLN18 is present, then all are required
9. P1920 - If either SLN19,SLN20 is present, then all are required
10. P2122 - If either SLN21,SLN22 is present, then all are required
11. P2324 - If either SLN23,SLN24 is present, then all are required
12. P2526 - If either SLN25,SLN26 is present, then all are required
13. P2728 - If either SLN27,SLN28 is present, then all are required

Semantics:

1. SLN01 is the identifying number for the subline item.
2. SLN02 is the identifying number for the subline level. The subline level is analogous to the level code used in a bill of materials.
3. SLN03 is the configuration code indicating the relationship of the subline item to the baseline item.
4. SLN08 is a code indicating the relationship of the price or amount to the associated segment.

Comments:

1. See the Data Element Dictionary for a complete list of IDs.
2. SLN01 is related to (but not necessarily equivalent to) the baseline item number. Example: 1.1 or 1A might be used as a subline number to relate to baseline number 1.
3. SLN09 through SLN28 provide for ten different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.



DTM Date/Time Reference

Pos: 205	Max: 1
Detail - Optional	
Loop: SLN	Elements: 2

User Option (Usage): Used

To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier Description: Code specifying type of date or time, or both date and time	M	ID	3/3	Must use
		Code Name				
		186 Invoice Period Start				
		187 Invoice Period End				
DTM02	373	Date Description: Date expressed as CCYYMMDD	X	DT	8/8	Used

Syntax:

1. R020305 - At least one of DTM02,DTM03,DTM05 is required
2. C0403 - If DTM04 is present, then all of DTM03 are required
3. P0506 - If either DTM05,DTM06 is present, then all are required



REF Reference Identification

Pos: 210	Max: >1
Detail - Optional	
Loop: SLN	Elements: 2

User Option (Usage): Used

To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier Description: Code qualifying the Reference Identification	M	ID	2/3	Must use
		Code Name				
		PO Purchase Order Number				
		RR2 Customer Service Reference				
		RR3 Partner Service Reference				
REF03	352	Description Description: A free-form description to clarify the related data elements and their content	X	AN	1/80	Used

Syntax:

1. R0203 - At least one of REF02,REF03 is required

Semantics:

1. REF04 contains data relating to the value cited in REF02.



PID Product/Item Description

Pos: 220	Max: 1000
Detail - Optional	
Loop: SLN	Elements: 6

User Option (Usage): Used

To describe a product or process in coded or free-form format

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PID01	349	Item Description Type Description: Code indicating the format of a description	M	ID	1/1	Must use
		Code Name F Free-form				
PID03	559	Agency Qualifier Code Description: Code identifying the agency assigning the code values	X	ID	2/2	Used
		Code Name ZZ Mutually Defined				
PID04	751	Product Description Code Description: A code from an industry code list which provides specific data about a product characteristic	X	AN	1/12	Used
PID05	352	Description Description: A free-form description to clarify the related data elements and their content	X	AN	1/80	Used
PID06	752	Surface/Layer/Position Code Description: Code indicating the product surface, layer or position that is being described	O	ID	2/2	Used
		Code Name ZZ Mutually Defined				
PID07	822	Source Subqualifier Description: A reference that indicates the table or text maintained by the Source Qualifier	O	AN	1/15	Used

Syntax:

1. C0403 - If PID04 is present, then all of PID03 are required
2. R0405 - At least one of PID04,PID05 is required
3. C0703 - If PID07 is present, then all of PID03 are required
4. C0804 - If PID08 is present, then all of PID04 are required
5. C0905 - If PID09 is present, then all of PID05 are required

Semantics:

1. Use PID03 to indicate the organization that publishes the code list being referred to.
2. PID04 should be used for industry-specific product description codes.
3. PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
4. PID09 is used to identify the language being used in PID05.



Comments:

1. If PID01 equals "F", then PID05 is used. If PID01 equals "S", then PID04 is used. If PID01 equals "X", then both PID04 and PID05 are used.
2. Use PID06 when necessary to refer to the product surface or layer being described in the segment.
3. PID07 specifies the individual code list of the agency specified in PID03.



TXI Tax Information

Pos: 237	Max: 10
Detail - Optional	
Loop: SLN	Elements: 2

User Option (Usage): Used

To specify tax information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TXI01	963	Tax Type Code Description: Code specifying the type of tax	M	ID	2/2	Must use
		Code Name				
		FT Federal Excise Tax				
		LO Local Tax (Not Sales Tax)				
		ST State Sales Tax				
TXI02	782	Monetary Amount Description: Monetary amount	X	R	1/18	Used

Syntax:

1. R020306 - At least one of TXI02, TXI03, TXI06 is required
2. P0405 - If either TXI04, TXI05 is present, then all are required
3. C0803 - If TXI08 is present, then all of TXI03 are required

Semantics:

1. TXI02 is the monetary amount of the tax.
2. TXI03 is the tax percent expressed as a decimal.
3. TXI07 is a code indicating the relationship of the price or amount to the associated segment.



Loop N1

Pos: 240	Repeat: 200
Optional	
Loop: N1	Elements: N/A

To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
240	N1	Name	O	1		Used
270	N4	Geographic Location	O	1		Used
280	REF	Reference Identification	O	12		Used



N1

Name

Pos: 240	Max: 1
Detail - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code Description: Code identifying an organizational entity, a physical location, property or an individual	M	ID	2/3	Must use
		Code Name OW Owner of Property or Unit				
N102	93	Name Description: Free-form name	X	AN	1/60	Used

Syntax:

1. R0203 - At least one of N102,N103 is required
2. P0304 - If either N103,N104 is present, then all are required

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.



N4 Geographic Location

Pos: 270	Max: 1
Detail - Optional	
Loop: N1	Elements: 3

User Option (Usage): Used

To specify the geographic place of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	City Name Description: Free-form text for city name	O	AN	2/30	Used
N402	156	State or Province Code Description: Code (Standard State/Province) as defined by appropriate government agency	O	ID	2/2	Used
N403	116	Postal Code Description: Code defining international postal zone code excluding punctuation and blanks (zip code for United States)	O	ID	3/15	Used

Syntax:

1. C0605 - If N406 is present, then all of N405 are required

Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.



REF Reference Identification

Pos: 280	Max: 12
Detail - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier Description: Code qualifying the Reference Identification	M	ID	2/3	Must use
		Code Name JD User Identification				
REF03	352	Description Description: A free-form description to clarify the related data elements and their content	X	AN	1/80	Used

Syntax:

1. R0203 - At least one of REF02,REF03 is required

Semantics:

1. REF04 contains data relating to the value cited in REF02.



TDS Total Monetary Value Summary

Pos: 010	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 4

User Option (Usage): Must use

To specify the total invoice discounts and amounts

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TDS01	610	Amount Description: Monetary amount	M	N2	1/15	Must use
TDS02	610	Amount Description: Monetary amount	O	N2	1/15	Used
TDS03	610	Amount Description: Monetary amount	O	N2	1/15	Used
TDS04	610	Amount Description: Monetary amount	O	N2	1/15	Used

Semantics:

1. TDS01 is the total amount of invoice (including charges, less allowances) before terms discount (if discount is applicable).
2. TDS02 indicates the amount upon which the terms discount amount is calculated.
3. TDS03 is the amount of invoice due if paid by terms discount due date (total invoice or installment amount less cash discount).
4. TDS04 indicates the total amount of terms discount.

Comments:

1. TDS02 is required if the dollar value subject to discount is not equal to the dollar value of TDS01.



TXI Tax Information

Pos: 020	Max: 10
Summary - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Used

To specify tax information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TXI01	963	Tax Type Code Description: Code specifying the type of tax	M	ID	2/2	Must use
		Code Name				
		FT Federal Excise Tax				
		LO Local Tax (Not Sales Tax)				
		ST State Sales Tax				
TXI02	782	Monetary Amount Description: Monetary amount	X	R	1/18	Used

Syntax:

1. R020306 - At least one of TXI02, TXI03, TXI06 is required
2. P0405 - If either TXI04, TXI05 is present, then all are required
3. C0803 - If TXI08 is present, then all of TXI03 are required

Semantics:

1. TXI02 is the monetary amount of the tax.
2. TXI03 is the tax percent expressed as a decimal.
3. TXI07 is a code indicating the relationship of the price or amount to the associated segment.



CTT Transaction Totals

Pos: 070	Max: 1
Summary - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Used

To transmit a hash total for a specific element in the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items Description: Total number of line items in the transaction set	M	N0	1/6	Must use
CTT02	347	Hash Total Description: Sum of values of the specified data element. All values in the data element will be summed without regard to decimal points (explicit or implicit) or signs. Truncation will occur on the left most digits if the sum is greater than the maximum size of the hash total of the data element. Example: -.0018 First occurrence of value being hashed. .18 Second occurrence of value being hashed. 1.8 Third occurrence of value being hashed. 18.01 Fourth occurrence of value being hashed. ----- 1855 Hash total prior to truncation. 855 Hash total after truncation to three-digit field.	O	R	1/10	Used

Syntax:

1. P0304 - If either CTT03,CTT04 is present, then all are required
2. P0506 - If either CTT05,CTT06 is present, then all are required

Comments:

1. This segment is intended to provide hash totals to validate transaction completeness and correctness.



SE Transaction Set Trailer

Pos: 080	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments Description: Total number of segments included in a transaction set including ST and SE segments	M	N0	1/10	Must use
SE02	329	Transaction Set Control Number Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M	AN	4/9	Must use

Comments:

1. SE is the last segment of each transaction set.



GE Functional Group Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To indicate the end of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GE01	97	Number of Transaction Sets Included Description: Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element	M	N0	1/6	Must use
GE02	28	Group Control Number Description: Assigned number originated and maintained by the sender	M	N0	1/9	Must use

Semantics:

1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

Comments:

1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header.



IEA Interchange Control Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To define the end of an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IEA01	116	Number of Included Functional Groups Description: A count of the number of functional groups included in an interchange	M	N0	1/5	Must use
IEA02	112	Interchange Control Number Description: A control number assigned by the interchange sender	M	N0	9/9	Must use