



Titan III

Alphanumeric Device



DISPLAY FORMAT

4 Line Display, with 20 characters per line, with user selectable option to view:

- 2 line display with 16 characters
- 2 line display with 20 characters

ADDRESS CAPCODES

16 address capability.

- Any combination of personal and maildrop group addresses

MESSAGE CAPACITY

20 message slots

- 6400 characters maximum for 20 message slots

MESSAGE STORAGE /MAIL DROP

A feature that enables the device to hold up to 15 group addresses with message history per address

- 19,200 character maximum for 15 group addresses

MESSAGE LOCK/PERSONAL INFORMATION FOLDER (PIF)

User can save/lock 10 messages

- 3200 characters maximum for 10 messages

REAL TIME CLOCK, WITH DATE AND DAY

Convenient real time display set via device menu

MESSAGE DATE AND TIME STAMPING

Tells when a message was received

MELODY/TONE ALERTS

Offers 7 melodies, 1 beep, 1 chirp, PLUS vibrate and sleep (no alert) options

ALARM CLOCK

User settable alarm clock allows an alarm to sound at a specific time daily, or to be set for 'one time only' use

USER-SELECTABLE REMINDER ALERT

User selectable option informs user that a message is unread and waiting

UNREAD MESSAGE INDICATION

Icons indicate which messages have not been read

CONTINUOUS MESSAGE INDICATION

Directs user to scroll down and finish reading the entire message

MESSAGE SCROLLING VIEW

User selectable feature that allows automatic scrolling through messages with one button push

- 3 levels of speed to choose from

MESSAGE FULL INDICATION WITH ICON

Alerts user that device has reached its limit of 20 messages/6400 characters and will begin to eliminate messages from oldest to newest

DUPLICATED MESSAGE INDICATION WITH ICON

Saves space by overwriting duplicated messages

ALL AND SELECTIVE MESSAGE ERASE

Allows user to delete a single unlocked message or all unlocked stored messages

AUTOMATIC MEMORY RETENTION

Retains unlocked messages for at least 30 seconds during battery replacement

BATTERY STATUS DISPLAY

Tells you when the battery is getting low and needs replacement

LOW BATTERY ALERT WITH INDICATOR

Indicates when battery is getting low and needs replacement

BATTERY

1 AAA battery (1.5 V) required

BACKLIGHTING DISPLAY

View messages in low light conditions

HOLSTER

Provides an easy way to keep device-and your messages-close at hand

SPECIFICATIONS

- Frequency Band 900 MHz
- Baud Availability 1600, 3200, 6400 FLEX
- Format - FLEX
- Receiver Type - Synthesized dimensions are correct
- Alert Tone 75 db @ 12 inch (30 cm) 2960 Hz on Standard Alert
- Operating Temperature -10 to +50 degrees Celsius (14 - 122 degrees Fahrenheit)
- Weight with Battery 1.6 oz. (45 grams)
- Dimensions 2 1/2" L x 1 1/2" H x 1/2" W (63L X 43.5H X 18.2W mm)

For more information, please contact your Arch Wireless representative or call 1-888-960-2724

